




Cable Trunking 電線槽



Type of cover :

Spring Capped Fixed Cover
(夾仔蓋)


KT + /standard code+ /SF

Turnbuckle Captive Screw Fixed Cover
(肚臍蓋)

KT + /standard code+ /QF


Screw Fixed Cover
(螺絲蓋)

KT + /standard code+ /SO



Two -Compartment
(分雙格)

KT + /standard code+ /2C



Three -Compartment
(分三格)

KT + /standard code+ /3C

Technical Specification:

- BS EN50085-1 or IEC61084-1
- Each length supplied with cover,coupler, tinned earth link and fixing screws.
- Standard length is 2.44m/Non standard thickness and finishes available to clients order.
- Customize size is available for order upon request.

Materials Standard:

- Galvanized Steel Sheet to BS4678
Part 1:Class 3 Protection to BS EN10143/
BS EN10346 (Coating Mass 275g/m²).
Standard product code +/GI
- Mild Steel Sheet to BS1449-1 or
BS EN10149-1 finished in Hot-dipped
Galvanized after Perforation to ISO1461
Standard product +/HDG
- Stainless Steel to Grade 304 or
Grade 316
Standard code +/SS304 or +/SS316

Other Material or Coating:

- Aluminum Steel Sheet
- Plastic Coated
- Epoxy / Polyester Powder Coated

Standard Size (mm) W x D	Available Material Thickness (mm)	Standard Code
50 x 50	1.0 / 1.2 / 1.4 / 1.6	5050
75 x 50	1.2 / 1.4 / 1.6	7550
75 x 75	1.2 / 1.4 / 1.6	7575
100 x 50	1.2 / 1.4 / 1.6	1050
100 x 75	1.2 / 1.4 / 1.6	1075
100 x 100	1.2 / 1.4 / 1.6	1010
150 x 50	1.2 / 1.4 / 1.6	1550
150 x 75	1.2 / 1.4 / 1.6 / 1.8	1575
150 x 100	1.2 / 1.4 / 1.6 / 1.8	1510
150 x 150	1.2 / 1.4 / 1.6 / 1.8	1515
200 x 50	1.2 / 1.4 / 1.6 / 1.8	2050
200 x 75	1.2 / 1.4 / 1.6 / 1.8	2075
200 x 100	1.2 / 1.4 / 1.6 / 1.8	2010
200 x 150	1.2 / 1.4 / 1.6 / 1.8	2015
200 x 200	1.4 / 1.6 / 1.8 / 2.0	2020
250 x 100	1.4 / 1.6 / 1.8 / 2.0	2510
250 x 150	1.4 / 1.6 / 1.8 / 2.0	2515
250 x 200	1.4 / 1.6 / 1.8 / 2.0	2520
250 x 250	1.4 / 1.6 / 1.8 / 2.0	2525
300 x 100	1.4 / 1.6 / 1.8 / 2.0	3010
300 x 150	1.4 / 1.6 / 1.8 / 2.0	3015
300 x 200	1.4 / 1.6 / 1.8 / 2.0	3020
300 x 300	1.4 / 1.6 / 1.8 / 2.0	3030
400 x 100	1.4 / 1.6 / 1.8 / 2.0	4010
400 x 150	1.4 / 1.6 / 1.8 / 2.0	4015
400 x 200	1.4 / 1.6 / 1.8 / 2.0	4020
400 x 250	1.4 / 1.6 / 1.8 / 2.0	4025
400 x 300	1.4 / 1.6 / 1.8 / 2.0	4030
400 x 400	1.4 / 1.6 / 1.8 / 2.0	4040