



## Cable **Tray** 電纜托盤









## CT Series 單摺邊

Light duty with single edge 13mm upstand to under 300mm (W) 20mm upstand to 300mm (W) or over Standard code CT / width / thickness

RCT Series 20/12 雙摺邊

Heavy duty with return edge 20mm upstand with 12mm return edge Standard code RCT / width / thickness

## **Technical Specification:**


- BS EN61537 or IEC61537 to class 5
- Each length supplied with coupler, tinned earth link and fixing screws.
- Standard length is 2.44m/ Non standard thickness and finishes available to clients order.
- Customize size is available for order upon request.


Materials Standard:


- Galvanized Steel Sheet to BS4678 Part 1: Class 3 Protection to BS EN10143 / BS EN10346 (Coating Mass 275g/m2) Standard product code +/GI
- Mild Steel Sheet to BS1449-1 or BS EN10149-1 finished in Hot-dipped Galvanized after Perforation to ISO1461 Standard product code  $+/{\rm HDG}$
- Stainless Steel to Grade 304 or Grade Standard product code  $\pm$ /SS304 or  $\pm$ / SS316

Other Material or Coating:

- Aluminum Steel Sheet
- Plastic Coated
- Epoxy / Polyester Powder Coated










35mm upstand with 15mm return edge Standard code

HCT / width / thickness



## HCT+ Series 50/25 雙摺邊

Extra Heavy duty with return edge 50mm upstand with 25mm return edge Standard code HCT / width / thickness-x